

**Installer : Save these instructions for future use!**

**FAILURE TO READ AND FOLLOW INSTRUCTIONS CAREFULLY BEFORE INSTALLATION OR OPERATION COULD DAMAGE THIS DEVICE OR CAUSE PROPERTY DAMAGE.**

## Keep Humidifiers Clean and Scale-Free!

### Description:

Steam-Treat is designed for humidifiers using up to 25 gallons per day and will inhibit scale for one season. Install Steam-Treat on the 1/4" food grade poly vinyl cold water tubing that supplies water directly to the humidifier. Equipped with John Guest Fittings.

### Application:

Clean tank and heating element and if necessary clean or install new pad before installing the Steam-Treat cartridge.

For best results humidifier should have a daily dump of water from the sump to diminish scale forming minerals.

Install a new Steam-Treat cartridge before each heating season.

Operating temperature, min./max, 40°-80°F (4-26°C).

### Installation Steps:

1. Shut off the water supply to your humidifier.
2. Disconnect existing cartridge or cut water tubing where new cartridge is to be installed.
3. **TAP INTO COLD WATER PIPE ONLY. DO NOT USE HOT WATER.**
4. Use 1/4" food grade poly vinyl water tubing only. (**DO NOT USE COPPER**) Insert the poly vinyl tubing directly into the John Guest fittings at each end of the Steam-Treat cartridge. No additional fittings or tools are necessary.
5. Observe proper direction of water flow.
6. Carefully turn on the water and check for leaks.
7. Check the Cartridge after approximately 8 hours for slight leaks not visible during original installation.

